NEW
NOUVEAUTÉ
NOVEDAD

X6.35 - X6.45 - X6.55

X6-T4 FINAL

ENGLISH
FRANÇAIS
ESPAÑOL




McCORMICK

ENGLISH

		X6.35	X6.45	X6.55
ENGINE				
TIER 4 FINAL		DEUTZ -AG	DEUTZ -AG	DEUTZ -AG
MAX. ENGINE POWER (ISO RATING)	HP/KW	110 / 81	119 / 88	126 / 93
RATED ENGINE POWER (ISO RATING)	HP/KW	105 / 77	113 / 83	120 / 88
RATED ENGINE SPEED	RPM	2200	2200	2200
MAX. TORQUE	NM	440	476	500
ENGINE RPM @ MAX. TORQUE	RPM	1600	1600	1600
BORE / STROKE	MM	98/120	98/120	98/120
DISPLACEMENT (CM^3) / NO. OF CYLINDERS		3600 / 4 TA	3600 / 4 TA	3600 / 4 TA
D.O.C.+S.C.R. EXHAUST SYSTEM				
ADBLUE TANK CAPACITY	L	20	20	20
FUEL TANK CAPACITY	L	150	150	150
CLUTCH				
MULTI-DISC WET CLUTCH				
DECLUTCH FUNCTION: BUTTON-OPERATED CLUTCH CONTROL				
TRANSMISSION				
SPEED FOUR + REVERSE POWER SHUTTLE: 12FWD+12REV				
SPEED FOUR + CREEPER + REVERSE POWER SHUTTLE: 16FWD+16REV				
XTRASHIFT + SPEED FOUR + REVERSE POWER SHUTTLE: 36FWD+12REV (3 POWERSHIFT SPEEDS)				
XTRASHIFT + SPEED FOUR + CREEPER + REVERSE POWER SHUTTLE: 48FWD+16REV				
REVERSE POWER SHUTTLE				
SHUTTLE MODULATION CONTROL: POTENTIOMETER FOR ADJUSTMENT OF POWER SHUTTLE RESPONSE				
PARK LOCK				
POWER TAKE-OFF				
WET MULTI-DISC PTO CLUTCH				
ELECTROHYDRAULIC ENGAGEMENT				
2 SPEEDS: 540/540E RPM				
2 SPEEDS: 540/1000 RPM				
4 SPEEDS: 540/540E/1000/1000E RPM				
1"3/8 (34.9MM) PTO SHAFT WITH 6 SPLINES				
1"3/8 (34.9MM) PTO SHAFT WITH 21 SPLINES				
GROUND SPEED PTO				
FRONT 4WD AXLE				
ELECTROHYDRAULIC 4WD ENGAGEMENT				
RIGID TYPE				
WITH ELECTRONICALLY-CONTROLLED HYDRAULIC SUSPENSIONS				
MAX. STEERING ANGLE		55°	55°	55°
ELECTROHYDRAULIC TWIN-LOCK DIFFERENTIAL LOCK				
BRAKING SYSTEM				
ANNULAR PISTON REAR BRAKES				
AUTOMATIC 4WD ENGAGEMENT ON BRAKING				
WET MULTI-DISC FRONT BRAKES				
IBS - INTEGRAL BRAKING SYSTEM				
HYDRAULIC TRAILER BRAKING				
PNEUMATIC TRAILER BRAKING				
HYDRAULIC SYSTEM				
CONTROL FUNCTIONS: DRAFT, POSITION, INTERMIX, FLOAT POSITION				
MECHANICAL CONTROL				
ERGONOMIC LIFT SYSTEM				
ELECTRONICALLY-CONTROLLED HITCH				
LIFT CAPACITY WITH 2 ASSISTOR RAMS	KG	6000	6000	6000
MAX. OPERATING PRESSURE	BAR	200	200	200
HYDRAULIC PUMP FLOW (HITCH + STEERING)	L/MIN	66 + 30	66 + 30	66 + 30
ADDITIONAL OIL TANK L		11	11	11
CAT. 2 THREE-POINT LINKAGE				
HYDRAULIC ADJUSTMENT OF TOP LINK AND RIGHT LIFTING ROD				
REMOTE VALVES STANDARD / OPTIONAL		2- 4	2- 4	2- 4
FRONT HITCH AND FRONT PTO (MAX. LIFT CAPACITY)	KG	2250	2250	2250
CAB AND DRIVING POSITION				
DELUXE SLIM CAB / RADIO ADAPTOR				
MECHANICAL CAB SUSPENSION				
HEATING / VENTILATION				
AIR-CONDITIONING				
AIR SUSPENSION SEAT				
RADIO / BLUETOOTH / MP3 READY				
DIGITAL INSTRUMENT PANEL				
12" DSM TOUCHSCREEN MONITOR				
ISOBUS ADAPTOR				
SATELLITE GUIDANCE KIT (8" MONITOR + ANTENNA)				
BUDDY SEAT + REFRIGERATOR IN-CAB STORAGE COMPARTMENT				
DIMENSIONS AND WEIGHTS				
LENGTH 4WD	MM	4176	4176	4176
MIN. WIDTH	MM	2075	2075	2075
WHEELBASE	MM	2420	2420	2420
HEIGHT OVER CAB	MM	2650	2650	2650
GROUND CLEARANCE	MM	420	420	420
WEIGHT IN RUNNING ORDER (WITHOUT BALLAST)	KG	4600	4600	4600
OPTIONAL EQUIPMENT				
10 FRONT BALLAST WEIGHTS 42 KG EACH				
300 KG FRONT WEIGHT FOR HITCH				

Key: ○ standard O option — non available

All data and illustrations provided in this brochure are for information purposes only and can be changed.



Les données techniques et les illustrations contenues dans cette publication sont fournie[illegible] d'information seulement et donc peuvent être modifiées sans préavis.